

Dulux Velocity UV Clear Backing Sealer, 405 – G0080

Velocity uv Clear Backing Sealer,

Product Code: 405-G0080

Specification met: Meets customer technical requirements.

Description

Velocity UV Clear Backing Sealer is a UV cured sealer for the backing of cement sheet.

Uses

Velocity UV Clear Backing Sealer is designed for roll coat application on a production line.

Performance Guide

Adhesion of primer	Excellent	Film Appearance	No defects in the dry film
Blocking	Excellent		

Product Guide

Colour	Clear	Specific gravity	1.13
Weight solids	100%	Volume solids	100%
Gloss Level	Low sheen	Shelf life	12 months when stored below 38°C
Viscosity	Approx 1000cp at 20°C		

Dulux Velocity UV Clear Backing Sealer, 405 – G0051

Application Data

Application Method	Roll Coater
Thinner	na
Clean Up	UV cleaner. Must use disposable polyethylene or nitrile gloves as acrylates are skin irritants.
Cure Schedule	10m/ min at 120 watt inch lamp
Dry time	Under uv lamps: 1 second
Cured Film Thickness	Recommended: 8-10 g /sqm dry film build

Theoretical spreading rate at recommended film thickness

A spreading rate of 100 m²/kg corresponds to 10g/sqm cured film thickness assuming no loss. Practical spreading rates will vary due to such factors as method and conditions of application and surface roughness.

Application Guide

Surface Preparation

Velocity UV Clear Backing Sealer should be applied over cement sheeting. Surfaces should be clean of any contaminants.

Application Procedure and Equipment

Roll Coater. One coat will achieve 8-10 g/sqm

Health and Safety

The SDS is an integral part of using this product as it contains information on the potential health effect of exposure, personal protective equipment needed and other relevant SH&E information.

For detailed information, refer to product label and the current Safety Data Sheet available through Sales and Customer Service Offices.

In the event of an emergency contact:	1 800 033 111 (ALL HOURS)	NZ 0800 734 607 (ALL HOURS)
--	-------------------------------------	---------------------------------------

Precautions and Limitations

- For optimum performance, ensure the minimum recommended dry film thickness is obtained.

Transport and Storage

Sizes:	20 Kilograms	Flashpoint:	n/a
Weight:	Approx. 21kg/188kg	UN:	3082
Dangerous Goods Class:	n/a	Package Group:	n/a
Shipment Name:	n/a		

Dulux Velocity UV Clear Backing Sealer, 405 - line

For further information contact:

Dulux Industrial Coatings
1-15 Pound Rd,
Dandenong South
Victoria, 3175
Australia
ACN 004 117 828

Telephone: 61 3 8787 4500

Fax: 61 3 8787 4542

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by Dulux Industrial Coatings in relation to goods manufactured by it or their use and application is given in good faith and is believed by Dulux Industrial Coatings to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Dulux Industrial Coatings provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Dulux Industrial Coatings by any condition or warranty implied by applicable legislation, regulation or other Government ordinance voiding or prohibiting such exclusion, limitation or modification