

Dulux Customcoat MP, 699 line

Customcoat MP, 699 Line

Product Code: 699-line
699G0078 Cream

Description

Customcoat MP produces an excellent primed surface for building products for interior and exterior use. Customcoat MP can be applied directly to the substrate to be primed.

Uses

Dulux Customcoat MP is designed for use as a primer on building products for both interior and exterior use.

Performance Guide

Film Appearance	No defects in the dry film
Adhesion	Excellent
Suitable substrates	MDF, and timber.

Product Guide

Colour	Various	Specific gravity	1.4-1.6
Shelf life	12 months when stored below 38°C	Volume solids	38 - 42%
Weight solids	58 - 62%		

Application Data

Application Method	Conventional spray, curtain coater, vacuum coater
Thinner	Water
Clean up	Water
Cure Schedule	Force dry or air dry

Cured Film Thickness Recommended: 30-40 µm dry film build

Theoretical spreading rate at recommended film thickness A spreading rate of 14 m²/litre corresponds to 35µm cured film thickness assuming no loss. Practical spreading rates will vary due to such factors as method and conditions of application and surface roughness.

Dulux Customcoat MP, 699 line

Application Guide

Surface Preparation

Surfaces should be clean of any contaminants.

Application Procedure and Equipment

Factory applied using conventional spray, curtain coat, or vacuum coat process

Health and Safety

The MSDS is an integral part of using this product as it contains information on the potential health effect of exposure, personal protective equipment needed and other relevant SH&E information.

For detailed information, refer to product label and the current Safety Data Sheet (no. 3986) available through Sales and Customer Service Offices.

Phone: Australia:- 13 24 99 New Zealand:- 09 828 1008.

Precautions and Limitations

- For optimum performance, ensure the minimum recommended dry film thickness is obtained

Transport and Storage

Sizes:	15L, 200L	Flashpoint:	n/a
Weight:	22kg, 300kg	UN:	n/a
Dangerous Goods Class:	n/a	Package Group:	n/a
Shipment Name:	n/a		

For further information contact:

	Dulux Industrial Coatings	Dulux New Zealand
	1-15 Pound Rd, Dandenong South Victoria, 3175 Australia ACN 004 117 828	31B Hillside Rd, Glenfield Auckland New Zealand
Telephone:	61 3 8787 4500	0800 800 424
Fax:	61 3 8787 4542	

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by Dulux Industrial Coatings in relation to goods manufactured by it or their use and application is given in good faith and is believed by Dulux Industrial Coatings to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Dulux Industrial Coatings provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Dulux Industrial Coatings by any condition or warranty implied by applicable legislation, regulation or other Government ordinance voiding or prohibiting such exclusion, limitation or modification