

# Dulux Customcoat Primer, 699 line

Customcoat Primer

**Product Code:** 69988200 Tan  
 699G0056 Grey  
 699G0084 White  
 699G0089 Cream

## Description

Customcoat Primer produces an excellent primed surface for building products for interior and exterior use. It may be used as a primer on building products on domestic and commercial buildings.

When top coated with Dulux Acrylic Industrial topcoat, it produces coated products with excellent exterior durability with high levels of colour retention and chalk resistance.

## Uses

Dulux Customcoat primer is designed for use as a primer on both timber based and cementitious building products. It can be applied directly to the substrate to be primed.

## Performance Guide

<b>Exterior Weathering</b>	Minimal change over the lifetime of the coating.	<b>Film Appearance</b>	No defects in the dry film
<b>15 year film integrity</b>	Excellent performance when top coated with Dulux Acrylic Industrial topcoat.	<b>Adhesion Substrate</b>	Excellent MDF, Timber, cement sheet
<b>15 year colour retention</b>	Superior colour retention when top coated with Dulux Acrylic Industrial topcoat		

## Product Guide

<b>Colour</b>	Various	<b>Specific gravity</b>	1.4-1.6
<b>Shelf life</b>	12 months when stored below 38°C	<b>Volume solids</b>	43-46%
<b>Weight solids</b>	62-65%		

# Dulux Customcoat Primer, 699 line

## Application Data

<b>Application Method</b>	Air atomised or airless spray, or vacuum coating.
<b>Thinner</b>	Water
<b>Clean up</b>	Water
<b>Cure Schedule</b>	Force dry or air dry
<b>Cured Film Thickness</b>	Recommended: 30-40 µm dry film build

**Theoretical spreading rate at recommended film thickness** A spreading rate of 12.7 m<sup>2</sup>/litre corresponds to 35µm cured film thickness assuming no loss. Practical spreading rates will vary due to such factors as method and conditions of application and surface roughness.

## Application Guide

### Surface Preparation

Surfaces should be clean of any contaminants.

### Application Procedure and Equipment

Factory applied using Air atomised or airless spray, or vacuum coat process

## Health and Safety

The SDS is an integral part of using this product as it contains information on the potential health effect of exposure, personal protective equipment needed and other relevant SH&E information.

For detailed information, refer to product label and the current Safety Data Sheet (no. 3667) available through Sales and Customer Service Offices.

Phone: Australia:- 13 24 99 New Zealand:- 09 828 1008.

## Precautions and Limitations

- For optimum performance, ensure the minimum recommended dry film thickness is obtained

## Transport and Storage

<b>Sizes:</b>	15L, 200L	<b>Flashpoint:</b>	n/a
<b>Weight:</b>	22kg, 300kg	<b>UN:</b>	n/a
<b>Dangerous Goods Class:</b>	n/a	<b>Package Group:</b>	n/a
<b>Shipment Name:</b>	n/a		



POWDER & INDUSTRIAL COATINGS

# Dulux Customcoat Primer, 699 line

**For further information contact:**

	<b>Dulux Industrial Coatings</b>	<b>Dulux New Zealand</b>
	1-15 Pound Rd, Dandenong South Victoria, 3175 Australia ACN 004 117 828	31B Hillside Rd, Glenfield Auckland New Zealand
<b>Telephone:</b>	61 3 8787 4500	0800 800 424
<b>Fax:</b>	61 3 8787 4542	

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

**DISCLAIMER:** Any advice, recommendation, information, assistance or service provided by Dulux Industrial Coatings in relation to goods manufactured by it or their use and application is given in good faith and is believed by Dulux Industrial Coatings to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Dulux Industrial Coatings provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Dulux Industrial Coatings by any condition or warranty implied by applicable legislation, regulation or other Government ordinance voiding or prohibiting such exclusion, limitation or modification